

安徽艾约塔硅油有限公司

Iota Silicone Oil(Anhui) Co., Ltd

安徽省蚌埠市高新区兴中路 985 号日月 Sunmoon industry park, 985 Xingzhong Road, Bengbu, China 科技园 233000

电话: 86-552-3827158 Tel: 86-552-3827158

传真: 86-552-3822922 Fax: 86-552-3822922

Silicone Gel IOTA 6250OCR

IOTA 6250OCR is a two-component addition molding organic silicon gel, which is suitable for full fitting of various vehicle screens, computer screens, tablet screens, etc.

Product features

- 1:1 mixed use, fast curing speed, heating can accelerate the curing speed
- The product has low viscosity and can quickly self level
- Low shrinkage rate
- It has excellent optical performance
- Good adhesion to the substrate

Product parameters

Inspection items	Component	Test Method	Results
Appearance	Α	Visual	Transparent
	В	Visual	Transparent
Viscosity (mpa.s)	Α	GB/T 2794	800~1200
	В	GB/T 2794	800~1200
Density (g/cm³)	Α	GB/T 13354	0.98±0.02
	В	GB/T 13354	0.98±0.02
Containing catalyst	В		
components			
Mixing ratio	A:B	/	1:1
Viscosity after mixing, mPa·s			800~1200
Operating time, min/25°C			≥15(or≥50)
Cone penetration (1/4			45-60
cone), 1/10mm			
Shear strength (glass glass),			> 0.2
MPa			
Positive tensile strength			> 0.2
(glass glass), MPa			

ADD: Sunmoon industry park, 985 Xingzhong Road, Bengbu, China 233000 Tel: 86-552-3827158; Fax: 86-552-3822922 Website: www.siliconeoil.net



安徽艾约塔硅油有限公司

Iota Silicone Oil(Anhui) Co., Ltd

安徽省蚌埠市高新区兴中路 985 号日月

Sunmoon industry park, 985 Xingzhong Road, Bengbu, China 233000

科技园 电话: 86-552-3827158

Tel: 86-552-3827158

传真: 86-552-3822922

Fax: 86-552-3822922

Yellowing index	< 0.2
Haze	< 0.2
Refractive index	1.405
Operating temperature,°C	-45 ~ 200°C

The data in the table is for reference only, please refer to the measured data

Operation and Safety

- Before potting, use alcohol, acetone and other suitable solvents to remove oil, dust and other dirt on the surface.
- Mix components A and B evenly in a weight ratio or volume ratio of 1:1 before use.
 You can mix them manually or with equipment. After mixing, quickly pour them into the product. Since this product cures quickly, it is recommended to remove bubbles by vacuum in order to obtain a better sealing effect.
- If the ratio of components A and B deviates greatly, the gel will be soft or hard. The ratio should be strictly 1:1.
- This product belongs to the addition curing system. The curing speed is only related to the temperature. Heating can accelerate the curing speed.
- Note that this product cannot come into contact with substances containing N, P, S,
 Sn, Pb, etc., otherwise it will cause the gel to not cure.
- Unused A and B adhesives should be stored in a sealed manner.
- Only A and B shipped in each batch of this product can be mixed. Mixing A and B shipped in different batches will affect the state after curing.
- IOTA 6250OCR is an addition-cured silicone rubber that contains neither toxic nor corrosive substances. Special handling precautions may be required and general industrial hygiene regulations should be followed.
- Wear protective gloves for prolonged or repeated contact.
- Keep away from heat/sparks/open flames, no smoking, and keep containers tightly closed. Use explosion-proof electrical/ventilation/lighting equipment.
- Transport as non-hazardous goods.

Package

A / B Component 20KG



安徽艾约塔硅油有限公司

Iota Silicone Oil(Anhui) Co., Ltd

Sunmoon industry park, 985 Xingzhong Road, Bengbu, China

安徽省蚌埠市高新区兴中路 985 号日月

科技园

Tel: 86-552-3827158

电话: 86-552-3827158 传真: 86-552-3822922

Fax: 86-552-3822922

A / B Component 180KG

Storage and Shelf life

Store in a dry place for a storage period of 12 months. If it expires, it needs to be retested and can be reused after passing the inspection.

This type of product belongs to non hazardous goods and can be transported as general chemicals.

ADD: Sunmoon industry park, 985 Xingzhong Road, Bengbu, China 233000 Tel: 86-552-3827158; Fax: 86-552-3822922 Website: www.siliconeoil.net