

## 安徽艾约塔硅油有限公司

# Iota Silicone Oil(Anhui) Co., Ltd

安徽省蚌埠市高新区兴中路 985 号日月 Sunmoon industry park, 985 Xingzhong Road, Bengbu, China 科技园

电话: 86-552-3827158

Tel: 86-552-3827158

传真: 86-552-3822922

Fax: 86-552-3822922

#### Silicone Gel IOTA 6650OCR

IOTA 6650OCR is a two-component addition molding silicone gel, which is suitable for the full fitting of various vehicle screens, computer screens, tablet screens, etc.

#### **Product features**

- 1:1 mixed use, fast curing speed, heating can accelerate the curing speed
- The product has low viscosity and can quickly self level
- Low shrinkage rate
- It has excellent optical performance
- Good adhesion to the substrate

#### 产品参数

Inspection items	Component	Test Method	Results
Appearance	Α	Visual	Transparent
	В	Visual	Transparent
Viscosity (mpa.s)	Α	GB/T 2794	800~1200
	В	GB/T 2794	800~1200
Density (g/cm³)	Α	GB/T 13354	0.98±0.02
	В	GB/T 13354	0.98±0.02
Containing catalyst	В		
components			
Mixing ratio	A:B	/	1:1
Viscosity after mixing, mPa·s			800~1200
Operating time, min/25°C			> 10
Cone penetration (1/4			35-45
cone), 1/10mm			
Shear strength (glass glass),			> 0.4
MPa			
Positive tensile strength			> 0.3
(glass glass), MPa			

ADD: Sunmoon industry park, 985 Xingzhong Road, Bengbu, China 233000 Tel: 86-552-3827158; Fax: 86-552-3822922 Website: www.siliconeoil.net



### 安徽艾约塔硅油有限公司

### Iota Silicone Oil(Anhui) Co., Ltd

安徽省蚌埠市高新区兴中路 985 号日月 Sunmoo 科技园

Sunmoon industry park, 985 Xingzhong Road, Bengbu, China 233000

电话: 86-552-3827158

Tel: 86-552-3827158

传真: 86-552-3822922

Fax: 86-552-3822922

Yellowing index		< 0.2
Haze		< 0.2
Light transmittance, 5		> 99
Refractive index		1.405
Operating temperature,°C		-45 ~ 200°C

The data in the table is for reference only, please refer to the measured data

#### **Operation and Safety**

- Before potting, use alcohol, acetone and other suitable solvents to remove oil, dust and other dirt on the surface.
- Mix components A and B in a weight ratio or volume ratio of 1:1 and use them. You
  can mix them manually or by equipment. After mixing, quickly pour them into the
  product. Since this product cures quickly, it is recommended to remove bubbles by
  vacuum in order to obtain a better sealing effect.
- If the ratio of components A and B deviates greatly, the gel will be soft or hard. The ratio should be strictly 1:1.
- This product belongs to the addition curing system. The curing speed is only related to the temperature. Heating can accelerate the curing speed.
- Note that this product should not be in contact with substances containing N, P, S,
   Sn, Pb, etc., otherwise it will cause the gel to not cure.
- Unused A and B rubber materials should be stored in a sealed manner.
- IOTA 6650OCR is an addition-cured silicone rubber that contains neither toxic nor corrosive substances. It may require special handling precautions and should comply with general industrial hygiene regulations.
- For long-term or repeated contact, wear protective gloves.
- Keep away from heat/sparks/open flames, no smoking, keep containers tightly closed. Use explosion-proof electrical/ventilation/lighting equipment.
- Transport as non-dangerous goods.

#### **Package**

- A / B Component 20KG
- A / B Component 180KG

ADD: Sunmoon industry park, 985 Xingzhong Road, Bengbu, China 233000 Tel: 86-552-3827158; Fax: 86-552-3822922 Website: www.siliconeoil.net



## 安徽艾约塔硅油有限公司

# Iota Silicone Oil(Anhui) Co., Ltd

安徽省蚌埠市高新区兴中路 985 号日月 Sunmoon industry park, 985 Xingzhong Road, Bengbu, China

科技园

Tel: 86-552-3827158

Fax: 86-552-3822922

电话: 86-552-3827158

传真: 86-552-3822922

### Storage and Shelf life

Store in a dry place for a storage period of 12 months. If it expires, it needs to be retested and can be reused after passing the inspection.

This type of product belongs to non hazardous goods and can be transported as general chemicals.

ADD: Sunmoon industry park, 985 Xingzhong Road, Bengbu, China 233000 Tel: 86-552-3827158; Fax: 86-552-3822922 Website: www.siliconeoil.net